


	Standard	Possible extras		
Technical data:				
Sound insulation:	Rw 35 dB (tested in SP laboratory)			
Heat insulation:	U=1,0 W/m²K (M10 x 21)			
Fire resistance:	EI30 (43 min, tested in SP laboratory)			
Door leaf:	Door leaf with thickness 62 ± 1 mm			
Edges:	Edges painted	Edges stained		
Decoration:	Flush	Decorative boards and/or slits		
Finish:	White paint (NCS S 0502-Y)	Different colors M161 - brown RAL3011 - brown red RAL7040 - window grey RAL6003 - olive green RAL5023 - distant blue Covered with TEAK cover veneer + (stain)+oil		
Gaskets:	Brown gasket White fire seal	Black fire seal		
Frame:	Softwood 42 x 105 mm			
Profile:	"VK450"	"VK450N"		
Finish:	painted white (NCS S 0502-Y)	Different colors M161 - brown RAL3011 - brown red RAL7040 - window grey RAL6003 - olive green RAL5023 - distant blue stained +oil		
Gaskets:	-			
Mounting hole:	Ø 16 mm; white plastic cap	Ø 16 mm; brown or beige plastic cap		
Threshold:	Oak 25 x 95 mm (type VK)	Oak (type VK)		
Locking system:	Lockcase: Abloy 4190 ASSA 565	Striking plate: 4690 1887-2	Lockcase: ASSA 2002 ASSA 8765 Abloy LC100 1769/20	Striking plate: 1887-2 1887-2 4690 E P/SEC S/S
Hinges:	Abloy 110 x 36 KSS ZN	Abloy 110 x 36 KSS JVA		
Dimensions:	Single-leaf M9 x 21 M10 x 21	Special dimensions up to M10 x 21		
Ironmongery:		Kick plate RST (polished, brushed) Door closer Dooreye (MS-, CR-glossy)		
Package:	Door leaf packed with frame. Edges covered with protective board and door coated with plastic.			




Inspecta
Vastavusserifikaat
ET-0056-13
Tule- ja helitökke
puituks FD14
**EI30
Rw 35dB**
AS Viljandi Aken ja Uks

2013
ID: T012345-1

STF
VTT-RTH-00075-11
Ääntä eristävä
puupalo-ovi FD14
EI,30/R,w,34dB
(ääniluokka 25dB)
AS Viljandi Aken ja Uks

2012
ID: T012345-1

SITAC
1002
Typgodkännandebevis
SC2434-12
Brand- och
ljuddörr FD14
EI30/R'w30

AS Viljandi Aken ja Uks

2013
ID: T012345-1

