



Inward opening double framed wooden-aluminium balcony door.

Air permeability

Class 4



## TECHNICAL DATA

|              |                                                                                                                 |
|--------------|-----------------------------------------------------------------------------------------------------------------|
| Size         | 680-880 x 1880-2180mm                                                                                           |
| Construction | double frame                                                                                                    |
| Opening      | side opening                                                                                                    |
| Frame        | pine, depth 130,170,210mm                                                                                       |
| Glass        | glass in outer sash up to 6mm, double glazing in inner sash up to 34mm                                          |
| Fittings     | long closure Abloy                                                                                              |
| Handle       | Fiskostar 501                                                                                                   |
| Finishing    | wood white (S 0502-Y), special color, unfinished or stained. Aluminium tone RAL9010 or according to colour card |
| Extras       | glued glazing bars, blinds                                                                                      |



FC06

It is possible to get special solutions. More information from the representative.

[vau.ee](http://vau.ee)



**MSEAL-B one sided**

|     | M7 | M8 | M9 |
|-----|----|----|----|
| M19 |    |    |    |
| M20 |    |    |    |
| M21 |    |    |    |
| M22 |    |    |    |

**MSEAL-B double sided**

min/max width x height

|     | M14 | M15 | M16 | M17 | M18 |
|-----|-----|-----|-----|-----|-----|
| M19 |     |     |     |     |     |
| M20 |     |     |     |     |     |
| M21 |     |     |     |     |     |
| M22 |     |     |     |     |     |

 recommended size range

**FC06**

