

Declaration of Performance

DoP: POAL v01v02

- Unique identification code of the product-type: **POAL1 v01-00, POAL1 v01-01, POAL1 v01-02, POAL1 v01-03, POAL1 v01-04, POAL1 v01-05, POAL1 v01-06, POAL1 v01-07, POAL1 v01-08, POAL1 v01-09, POAL1 v01-10, POAL1 v01-11, POAL1 v01-12, POAL1 v01-13, POAL1 v01-14, POAL1 v01-15, POAL1 v01-16, POAL1 v01-17, POAL1 v01-18, POAL1 v01-19, POAL1 v01-20, POAL1 v01-21, POAL1 v01-22, POAL1 v01-23, POAL1 v01-24, POAL1 v01-25, POAL1 v01-26, POAL1 v01-27, POAL1 v01-28, POAL1 v01-29, POAL1 v01-30, POAL2 v01-00**
- Product: **Balcony door**
- Intended use or uses of the construction product: **in domestic and commercial locations**
- Manufacturer: **AS Viljandi Aken ja Uks
Puidu 6, 71020 Viljandi, Estonia
Tel. (+372) 433 0610
E-Mail: vau@vau.ee**
- System or systems of assessment and verification of constancy of performance of the construction product: **system 3**
- Harmonised standard: **EN 14351-1:2006+A2:2016**
- Notified body: initial type testing performed by NB and issued test/calculation reports:
**NB 1526 TÜV Estonia Ltd
NB 0809 VTT Technical Research Centre of Finland**
- Declared performance:

Product	Watertightness	Dangerous substances	Resistance to wind load - test pressure	Resistance to wind load - frame deflection	Load-bearing capacity of safety devices	Acoustic performance	Thermal transmittance	Air permeability
POAL1 v01-00	npd	npd	npd	npd	npd	npd	npd	4
POAL1 v01-01	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-02	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-03	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-04	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-05	9A	npd	4	C	npd	40 dB (-1;-3)	0,9	4
POAL1 v01-06	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-07	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-08	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-09	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-10	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-11	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-12	9A	npd	4	C	npd	40 dB (-1;-3)	0,9	4
POAL1 v01-13	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-14	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-15	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-16	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-17	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-18	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-19	9A	npd	4	C	npd	40 dB (-0;-2)	0,9	4
POAL1 v01-20	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-21	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-22	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-23	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-24	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-25	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-26	9A	npd	4	C	npd	40 dB (-0;-2)	0,9	4
POAL1 v01-27	9A	npd	4	C	npd	npd	0,9	4
POAL1 v01-28	9A	npd	4	C	npd	npd	0,9	4

POAL1 v01-29	9A	npd	4	C	npd	npd	0,8	4
POAL1 v01-30	9A	npd	4	C	npd	npd	0,8	4
POAL2 v01-00	npd	npd	npd	npd	npd	npd	npd	4

Note! npd: *no performance determined.*

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Veiko Põldsaar
R&D Manager
22.02.2017