

## Declaration of Performance

DoP: ED78-T1v01

- Product type code: **ED78-T1**
- Product: **External door**
- Intended use or uses of the construction product: **in domestic and commercial locations**
- Manufacturer: **AS Viljandi Aken ja Uks  
Puidu 6, 71020 Viljandi, Estonia  
Tel. (+372) 433 0610  
E-Mail: vau@vau.ee**
- System or systems of assessment and verification of constancy of performance of the construction product: **system 3**
- Harmonised standard: **EN 14351-1:2006+A2:2016**
- Notified body: initial type testing performed by NB and issued test/calculation reports:  
**NB 1526** TÜV Estonia Ltd  
**NB 0809** Eurofins Expert Services Oy
- Declared performance:

Product	IGU	Watertightness	Dangerous substances	Resistance to wind load - test pressure	Resistance to wind load - frame deflection	Load-bearing capacity of safety devices	Acoustic performance	Thermal transmittance	Air permeability
ED78-T1	-	7B	npd	3	C	npd	npd	0,67	4
ED78-T1/vk-01	4S-14air-4-14air-4S	7B	npd	3	C	npd	npd	0,74	4
ED78-T1/vk-02	4S-14-4-14-4S	7B	npd	3	C	npd	npd	0,77	4
ED78-T1/vk-03	4Se-14-4-14-4Se	7B	npd	3	C	npd	npd	0,76	4
ED78-T1/vk-04	6S-12-4-12-6S	7B	npd	3	C	npd	npd	0,79	4
ED78-T1/vk-05	6Se-12-4-12-6Se	7B	npd	3	C	npd	npd	0,78	4
ED78-T1/vk-06	4S-18-4-18-4S	7B	npd	3	C	npd	npd	0,76	4
ED78-T1/vk-07	4Se-18-4-18-4Se	7B	npd	3	C	npd	npd	0,75	4
ED78-T1/vk-08	6S-16-4-16-6S	7B	npd	3	C	npd	npd	0,76	4
ED78-T1/vk-09	6Se-16-4-16-6Se	7B	npd	3	C	npd	npd	0,75	4
ED78-T1/vk-10	6Se-14-4-14-44.4Se	7B	npd	3	C	npd	npd	0,77	4
ED78-T1/sk-01	4S-14-4-14-4S	7B	npd	4	C	npd	npd	0,86	4
ED78-T1/sk-02	4Se-14-4-14-4Se	7B	npd	3	C	npd	npd	0,82	4
ED78-T1/sk-03	6S-12-4-12-6S	7B	npd	3	C	npd	npd	0,92	4
ED78-T1/sk-04	6Se-12-4-12-6Se	7B	npd	3	C	npd	npd	0,89	4
ED78-T1/sk-05	4S-18-4-18-4S	7B	npd	3	C	npd	npd	0,78	4
ED78-T1/sk-06	4Se-18-4-18-4Se	7B	npd	3	C	npd	npd	0,74	4
ED78-T1/sk-07	6S-16-4-16-6S	7B	npd	3	C	npd	npd	0,81	4
ED78-T1/sk-08	6Se-16-4-16-6Se	7B	npd	3	C	npd	npd	0,78	4
ED78-T1/sk-09	6Se-14-4-14-44.4Se	7B	npd	3	C	npd	npd	0,82	4

Note! npd: no performance determined.

r - Chromatech Ultra F  
S - energy glass 1,1  
Se - energy glass 1,0

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Veiko Põldsaar  
R&D Manager  
20.09.2022

