

Declaration of Performance

DoP: ED178-T2-60v03

- Product type code: **ED178-T2-60**
- Product: **external fire resistance door**
- Intended use or uses of the construction product: **in domestic and commercial locations**
- Manufacturer: **AS Viljandi Aken ja Uks**
Puidu 6, 71020 Viljandi, Estonia
Tel. (+372) 433 0610
E-Mail: vau@vau.ee

- System or systems of assessment and verification of constancy of performance of the
- construction product: **system 1 and 3**

- Harmonised standard: **EN 16034:2014**
EN 14351-1:2006+A2:2016

- Notified body: initial type testing performed by NB and issued test/calculation reports:

System:	1	NB 1336	Kiwa Estonia OÜ
	3	NB 1526	TÜV Estonia Ltd
		NB 0809	Eurofins Expert Services Oy

- Declared performance:

Product	IGU	System 1			System 3					
		Fire resistance - E, EI, EI ₂ , EW (EN 13501-2)	Smoke resistance (EN 13501-2)	Self-closing (EN 13501-2)	Watertightness (EN 12208)	Resistance to wind load - test pressure (EN 12210)	Resistance to wind load - frame deflection (EN 12210)	Acoustic performance dB (EN ISO 717-1)	Thermal transmittance W/m ² K (EN ISO 10077-1)	Air permeability (EN 12207; EN 14351-1)
ED178-T2-01	-	EI 60	Sa4/ S ₂₀₀	C5	7B	3	C	38 dB	0,84	4
ED178-T2/vk-01	P 44.218r14 Se+Py60	EI 60	Sa4/ S ₂₀₀	C5	7B	3	C	40 dB	1,0	4
ED178-T2/vk-02	P 44.2418r12+12 S+S+Py60	npd	npd	npd	7B	3	C	npd	0,96	4
ED178-T2/vk-03	P 44..146r12+10 S+Kir+S	npd	npd	npd	7B	3	C	npd	0,95	4
ED178-T2/vk-04	P 44..146r12+10 Se+Kir+Se	npd	npd	npd	7B	3	C	npd	0,97	4
ED178-T2/vk-05	P 44..1444..1r10+10 S+Kir+S	npd	npd	npd	7B	3	C	npd	0,96	4

ED178-T2/vk-06	P 44..1444..1r10+10 Se+Kir+Se	npd	npd	npd	7B	3	C	npd	0,96	4
ED178-T2/sk-01	P 44.218r14 Se+Py60	EI 60	Sa4/ S ₂₀₀	C5	7B	3	C	41 dB	1,31	4
ED178-T2/sk-02	P 44.2418r12+12 S+S+Py60	npd	npd	npd	7B	3	C	npd	1,03	4
ED178-T2/sk-03	P 44..146r12+10 S+Kir+S	npd	npd	npd	7B	3	C	npd	1,07	4
ED178-T2/sk-04	P 44..146r12+10 Se+Kir+Se	npd	npd	npd	7B	3	C	npd	1,11	4
ED178-T2/sk-05	P 44..1444..1r10+10 S+Kir+S	npd	npd	npd	7B	3	C	npd	1,1	4
ED178-T2/sk-06	P 44..1444..1r10+10 Se+Kir+Se	npd	npd	npd	7B	3	C	npd	1,03	4

Note! npd: *no performance determined.*

vk - small glass opening

sk - large glass opening

r - warm spacer Chromatech Ultra F

S - energy glass 1,1

Se - energy glass 1,0

9. The performance of the product identified in points 1 and 2 is in conformity with the declared
This declaration of performance is issued under the sole responsibility of the manufacturer

Signed for and on behalf of the manufacturer by:

Veiko Põldsaar

R&D Manager

23.04.2026

